MIRAI

experience the future

DML-619N200

19” / 48 cm LCD MONITOR

TCO Development TCO'03 DISPLAYS www.tcodevelopment.com

DVI with

700 : 1 Contrast

300 cd/m² Luminance

5 ms Ultra Fast

MIRAI
experience the future

DML-619N200
19"/48 cm LCD Monitor

Screen Size	376.32(H) x 301.056(V)
Driver Element	a-si TFT Active Matrix
Aspect Ratio	4 : 3
Pixel Pitch	0.294(H) x 0.294(V)mm
Panel Resolution	1280 x 1024
Brightness	300 cd/m^2
Contrast Ratio (typ.)	700 : 1
Response Time (typ.)	5 ms
Viewing Angles (typ.)	150°(H) / 140°(V)
Display Color	16.2 M
Horizontal Sync.	30-83kHz
Vertical Sync.	50-75Hz
Input Connector	D-Sub mini 15 pins, DVI-D 24 pins
Auto Adjust	Clock, Phase, H-Position, V-Position
Screen Scaling	VGA/SVGA/XGA/SXGA Full Screen Display
Speaker	1W x 2
Power Management	VESA DPMS, DVI DMPM
Safety	TCO03 / TUV-GS / CE / CB / Nemko
COLOUR Temperature	User, 6500K, 7500K, 9300K
Power Input	AC 100-240 V (Worldwide) 50-60 Hz
Operation Mode	37 W
Stand-by & Suspend Mode	<2 W @230VAC 50Hz
Active-off Mode	<1 W @230VAC 50Hz
Video Frequency Bandwidth	135 MHz dot clock
Dimension	438mm(W) x 551.5mm(H) x 243mm(D)
Weight	7.8 kg

Jupiterstraat 106, 2132 HE Hoofddorp, The Netherlands
TEL +31 (0)23-567 10 58 FAX +31 (0)23-567 10 67
info@nl-mirai.com